



## Control Panel Overlays

- Harsh-environment resistant
- Different thicknesses and finishes available
- Completely customizable
- Abrasion and water resistant

## Description

Our Control Panel Overlays are customizable with materials, thicknesses, colors, cutouts, transparent windows, embossed buttons and adhesives—making them adaptable to a wide variety of environments and applications. The overlays are dimensionally stable and form a protective barrier between the environment and your equipment.

## Additional information



Model Number	WFS-OS-OVERLAY Control Panel Overlay
Applications	Medical Equipment, Electronic Equipment & Devices, Harsh Environments, Product Marking
Material	Lexan®
Overall Thickness	10.0 mil ± 10%
Expected Outdoor Life	3 - 10 years
Temperature Service Range	-40° F to 302° F
Minimum Application Temperature	50° F
Water Resistance	Excellent
Oil Resistance	Good
Solvents Resistance	Fair
UV Resistance	Fair
Abrasion Resistance	Excellent
Adhesive	Clear Acrylic
Adhesion	Adhesion to HSE Plastics: Good, Adhesion to LSE Plastics: Poor, Adhesion to Glass at 72 hr. dwell: Good, Adhesion to Steel at 72 hr. dwell: Excellent
Shelf Life	1 Year, Stored at 70F and 50% Relative Humidity